



TOUCHMILL

TOUCHMILL
C/CAR

for leather, for you

TOUCHMILL C/CAR

TOUCHMILL C/CAR

Characteristics

Appearance	Amber liquid
Total solids	About 44%
pH 10%	Approx. 6

Description

Oils, emulsifiers and penetrators emulsion.

Properties

For use on automotive hides. Fogging tests are not affected. It helps to soften the leathers.
For use on crust or finished leathers (after fixing).

Application

Roller coating machine.

Use

It is advised for use on crust leathers by roller coating. Dilute the product 1:1 in warm water and apply on the flesh side.
Rest 24 hours then stake.

Smart use

Can be used together with our flesh side binder "REFLEX SR 200" to combine softening and dust binding properties in a single use.

Do not store below 5°C

Do not store above 40°C



The characteristics shown on this data sheet are only provided as a guide. Product specifications are available upon request.

COMPANY WITH
MANAGEMENT SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =
= ISO 14001 =
= OHSAS 18001 =



TOUCHMILL C/CAR

SOFTENER FOR AUTOMOTIVE LEATHER
Touchmill, a technology that goes beyond leather and
that stands for quality and excellence.

INNOVATIVE AND ECO-FRIENDLY PRODUCT

No fogging alteration.
No migration.
No finishing adhesion issues.

GSC GROUP SPA

- ◆ COMPLETE OFFER OF CHEMICAL SOLUTIONS FOR LEATHER PRODUCTION
- ◆ HIGH-QUALITY PRODUCTION
- ◆ OUTSTANDING EXPERTISE IN TECHNICAL ASSISTANCE FOR THE TANNING INDUSTRY



Via dell'Industria, 5 36054 Montebello Vic.no (VI)
Italy

Tel. +39 0444 670949 - 671061

Fax +39 0444 670321

info@gscspa.it

www.gscspa.com